

# WEEBILL 3S Camera Compatibility List



Update on September 06, 2023 (Firmware version V1.70)

V1.04

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	5DS, 5DS R, 5D Mark III, 5D Mark IV, 6D Mark II, 6D, 90D, 80D, EOS 850, EOS 800D, R50, R8, 200D II	EF 16-35mm f/4L IS USM	Camera and lens	√	√	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		EF 16-35mm f/2.8L III USM	Camera and lens	√	√	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
		EF 17-40mm f/4L USM	Camera and lens	√	√	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D Mark II、 6D、 90D、 80D、 EOS 850、 EOS 800D、 R50、 R8、 200D II	EF 24-70mm f/2.8L II USM	Camera and lens	√	√	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
		EF 24-70mm f/4L IS USM	Camera and lens	√	√	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
		EF 24-105mm f/4L IS II USM	Camera and lens	√	√	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	√	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	-	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at 24-50mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D、 90D、 80D、 EOS 850、 EOS 800D、 R50、 R8、 200D II	EF 24mm f/1.4L II USM	Camera and lens	√	√	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		No need to remove eyepiece cap
		EF 35mm f/1.4L II USM	Camera and lens	√	√	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		No need to remove eyepiece cap
		EF 50mm f/1.4 USM	Camera and lens	√	√	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		No need to remove eyepiece cap
		EF 85mm f/1.4L IS USM	Camera and lens	√	√	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		No need to remove eyepiece cap
		EF 85mm f/1.8 USM	Camera and lens	√	√	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	5DS、 5DS R、 5D Mark III、 5D Mark IV、 6D Mark II、 6D、 90D、 80D、 EOS 850、 EOS 800D、 R50、 R8、 200D II	Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		No need to remove eyepiece cap
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark	
				Horizontal	Vertical	Horizontal	Vertical			
Canon	EOS R, EOS R5, EOS R6, EOS R6 Mark II	EF 16-35mm f/4L IS USM	Camera and lens	√	√	√	√		Can be balanced at any focal length, do not remove eyepiece cap	
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, do not remove eyepiece cap	
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
		EF 16-35mm f/2.8L III USM	Camera and lens	-	-	-	-			
			with zoom/focus motor (for focus control)	-	-	-	-			
			with zoom/focus motor (for zoom control)	-	-	-	-			
			with transmission transmitter	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-			
		EF 17-40mm f/4L USM	Camera and lens	√	√	√	√			Can be balanced at any focal length, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side		Can be balanced at any focal length, do not remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side		Can be balanced at any focal length, do not remove eyepiece cap
			with transmission transmitter	√	-	√	-			Can be balanced at any focal length, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-			
		EF 24-70mm f/2.8L II USM	Camera and lens	-	-	-	-			
			with zoom/focus motor (for focus control)	-	-	-	-			
			with zoom/focus motor (for zoom control)	-	-	-	-			
			with transmission transmitter	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-			

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS R, EOS R5, EOS R6, EOS R6 Mark II	EF 24-70mm f/4L IS USM	Camera and lens	√	√	√	√		Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		EF 24-105mm f/4L IS II USM	Camera and lens	√	√	√	√		Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	√	√	√		Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		EF 24mm f/1.4L II USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 35mm f/1.4L II USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS R, EOS R5, EOS R6, EOS R6 Mark II	EF 35mm f/1.4L II USM	with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 50mm f/1.2L USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 50mm f/1.4 USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 85mm f/1.4L IS USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		EF 85mm f/1.8 USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS R, EOS R5, EOS R6, EOS R6 Mark II	Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	√	-		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	√	-		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		RF 24-70mm f/2.8 L IS USM	Camera and lens	√	√	√	√		Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
		RF 15-35mm f/2.8 L IS USM	Camera and lens	√	√	√	√		Can be balanced at any focal length, No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		RF50mm F1.2 L USM	Camera and lens	√	-	√	-		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark	
				Horizontal	Vertical	Horizontal	Vertical			
Canon	EOS R, EOS R5, EOS R6, EOS R6 Mark II	EF 16-35mm f/4L IS USM	Camera and lens	√	√	√	√		Can be balanced at any focal length, do not remove eyepiece cap	
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, do not remove eyepiece cap	
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, do not remove eyepiece cap	
		EF 16-35mm f/2.8L III USM	Camera and lens	-	-	-	-			
			with zoom/focus motor (for focus control)	-	-	-	-			
			with zoom/focus motor (for zoom control)	-	-	-	-			
			with transmission transmitter	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-			
		EF 17-40mm f/4L USM	Camera and lens	√	-	√	-			Can be balanced at any focal length, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side		Can be balanced at any focal length, do not remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side		Can be balanced at any focal length, do not remove eyepiece cap
			with transmission transmitter	√	-	√	-			Can be balanced at any focal length, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-			
		EF 24-70mm f/2.8L II USM	Camera and lens	-	-	-	-			
			with zoom/focus motor (for focus control)	-	-	-	-			
			with zoom/focus motor (for zoom control)	-	-	-	-			
			with transmission transmitter	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-			
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-			

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS RP, EOS R7, EOS R10	EF 24-70mm f/4L IS USM	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		EF 24-105mm f/4L IS II USM	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		EF 24mm f/1.4L II USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 35mm f/1.4L II USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS RP, EOS R7, EOS R10	EF 35mm f/1.4L II USM	with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 50mm f/1.2L USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 50mm f/1.4 USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		EF 85mm f/1.4L IS USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		EF 85mm f/1.8 USM	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS RP, EOS R7, EOS R10	Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	√	√	√		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
		RF 24-70mm f/2.8 L IS USM	Camera and lens	√	√	√	√		Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
		RF 15-35mm f/2.8 L IS USM	Camera and lens	√	√	√	√		Can be balanced at any focal length, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		RF50mm F1.2 L USM	Camera and lens	√	-	√	-		Do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Do not remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS M50, EOS M6 Mark II	EF-M 32mm f/1.4 STM	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		
		EF-M 11-22mm f/4-5.6 IS STM	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-		
			with zoom/focus motor (for zoom control)	√	-	√	-		
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		
		EF-M 15-45mm f/3.5-6.3 IS STM	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-		
			with zoom/focus motor (for zoom control)	√	-	√	-		
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		
		EF-M 18-55mm f/3.5-5.6 IS STM	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-		
			with zoom/focus motor (for zoom control)	√	-	√	-		
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Canon	EOS M50, EOS M6 Mark II	EF-M 55-200mm f/4.5-6.3 IS STM	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-		
			with zoom/focus motor (for zoom control)	√	-	√	-		
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		
		EF-M 22mm f/2 STM	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-		
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		
		EF-M 28mm f/3.5 IS STM	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-		
	with transmission transmitter		√	-	√	-			
	with transmission transmitter and zoom/focus motor (for focus control)		√	-	√	-			

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850, D780	AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850, D780	AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
with transmission transmitter	√		-	√	-		No need to remove eyepiece cap		
with transmission transmitter and zoom/focus motor (for focus control)	√		-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap		



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	D850, D780	AF-S NIKKOR 85mm f/1.4G	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		AF-S NIKKOR 85mm f/1.8G	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		Sigma 24-70mm f/2.8L DG	Camera and lens	√	-	√	-		Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		Sigma 35mm F1.4 DG	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 50mm F1.4 DG	Camera and lens	√	-	√	-		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
with transmission transmitter	√		-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap		
with transmission transmitter and zoom/focus motor (for focus control)	√		-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z fc, Z50, Z5, Z6, Z6 II, Z7, Z7 II, Z30, Z50	NIKKOR Z 24-70mm f/2.8S	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		NIKKOR Z 24-70mm f/4S	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
		NIKKOR Z 35mm f/1.8S	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		NIKKOR Z 50mm f/1.8S	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z fc, Z50, Z5, Z6, Z6 II, Z7, Z7 II, Z30, Z50	AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z fc, Z50, Z5, Z6, Z6 II, Z7, Z7 II, Z30, Z50	AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
		AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z fc, Z50, Z5, Z6, Z6 II, Z7, Z7 II, Z30, Z50	Sigma 24-70mm f/2.8L DG	Camera and lens	√	√	√	√		Can be balanced at 24mm, do not remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	-	√	-		Can be balanced at 24mm, do not remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		Sigma 35mm F1.4 DG	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 50mm F1.4 DG	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z8	NIKKOR Z 24-70mm f/2.8S	Camera and lens	√	√	√	√		Landscape: eyepiece cap slightly rubs against the camera at 24-35mm. Portrait: can be balanced at any focal length
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Landscape: eyepiece cap slightly rubs against the camera at 24-35mm. Portrait: can be balanced at any focal length
			with zoom/focus motor (for zoom control)	-	-	-	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	-	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		NIKKOR Z 24-70mm f/4S	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		Can be balanced at any focal length, no need to remove eyepiece cap
		NIKKOR Z 35mm f/1.8S	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		NIKKOR Z 50mm f/1.8S	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z8	AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z8	AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Nikon	Z8	AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap
		Sigma 24-70mm f/2.8L DG	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		Sigma 35mm F1.4 DG	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 50mm F1.4 DG	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX30、 ZV-1 II	FE 16-35mm F2.8 GM	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 12-24mm F4 G	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		FE 24mm f1.4GM	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX30、 ZV-1 II	FE 24-70mm F2.8 GM	Camera and lens	√	√	√	√		Can be balanced at any focal length, need to remove eyepiece cap (Roll axis slightly rubs against the camera)
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap (Roll axis slightly rubs against the camera)
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap (Roll axis slightly rubs against the camera)
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, need to remove eyepiece cap (Roll axis slightly rubs against the camera)
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap (Roll axis slightly rubs against the camera)
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, need to remove eyepiece cap (Roll axis slightly rubs against the camera)
		FE 24-70mm F4 ZA OSS	Camera and lens	√	√	√	√		Can be balanced at 24-50mm, need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24-50mm, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24-50mm, need to remove eyepiece cap
		FE 28mm F2	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		FE 50mm F1.8	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX30、 ZV-1 II	FE 85mm F1.4 GM	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		No need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	No need to remove eyepiece cap
		E 10-18mm F4 OSS	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、 α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX30、 ZV-1 II	E PZ 18-105mm F4 G OSS	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		Sigma 50mm f/1.4 DG	Camera and lens	√	√	√	√		No need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	No need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Sony	α1、 α9、 α9 II、 α7M2、 α7R2、 α7S2、 α7M3、 α7M4、 α7R3、 α7S3、 α7R4、 α7R5、 α7C、	Tamron 28-75mm f/2.8	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
	α6600、 α6500、 α6400、 α6300、 α6100、 ZV -E10、 ZV -E1、 ZV -1、 ILME-FX3、 FX30、 ZV-1 II	sigma18-35mm f/1.8 DC HSM Art (+Canon adapter ring)	Camera and lens	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
FUJIFILM	X-T3, X-T4, X-T5, X-H2s, X-S20	XF 16-55mm f/2.8 R LM WR	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		XF 18-55mm f/2.8-4 R OIS	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		XF 35mm f/2 R WR	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark		
				Horizontal	Vertical	Horizontal	Vertical				
FUJIFILM	X-T3, X-T4, X-T5, X-H2s, X-S20	XF 56mm f/1.2 R	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap		
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
		XC 15-45mm f/3.5-5.6 OIS	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap		
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
		Super EBC XF 23mm f/1.4 R	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap		
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
		Panasonic	G9, GH5s, GH5, GH6	Vario-Elmarit 8-18mm f/2.8-4.0	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
					with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
with zoom/focus motor (for zoom control)	√				-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
with transmission transmitter	√				-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap		
with transmission transmitter and zoom/focus motor (for focus control)	√				-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		
with transmission transmitter and zoom/focus motor (for zoom control)	√				-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap		



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Panasonic	G9, GH5s, GH5, GH6	Vario 12-35mm f/2.8 II	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		Lumix G 25mm f/1.7	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		MACRO 30mm f/2.8	Camera and lens	√	√	√	√		Can be balanced at any focal length, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at any focal length, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at any focal length, no need to remove eyepiece cap
		sigma 18-35mm f/1.8 DC HSM Art (+adapter ring)	Camera and lens	√	√	√	√		Need to remove eyepiece cap
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
Panasonic	S5	LUMIX S 24-105mm F/4 Macro OIS	Camera and lens	√	√	√	√		Can be balanced at 24mm, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
		LUMIX S PRO 24-70mm f/2.8	Camera and lens	√	√	√	√		Can be balanced at 24mm, no need to remove eyepiece cap
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
			with transmission transmitter	√	-	√	-		Can be balanced at 24mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	Can be balanced at 24mm, no need to remove eyepiece cap
	S1, S1H	LUMIX S 24-105mm F/4 Macro OIS	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		



Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMCC 4K	Vario-Elmarit 8-18mm f/2.8-4.0	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		Vario 12-35mm f/2.8 II	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		G Vario 12-32mm 0.2m/0.66ft	Camera and lens	-	-	-	-		
			with zoom/focus motor (for zoom control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for zoom control)	-	-	-	-		
		25mm f/1.7	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPCC 4K	MACRO 30mm f/2.8	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		D-Dreamer 12mm F2.8	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
	BMPCC 6K	EF 24mm f/1.4L II USM	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
		EF 35mm f/1.4L II USM	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
EF 50mm f/1.4L USM	Camera and lens	-	-	-	-				
	with zoom/focus motor (for focus control)	-	-	-	-				
	with transmission transmitter	-	-	-	-				
	with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-				

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment		Camera Backing Base		Servo Zoom/Focus Motor	Installation Remark
				Horizontal	Vertical	Horizontal	Vertical		
BMD	BMPCC 6K	EF 85mm f/1.8L USM	Camera and lens	-	-	-	-		
			with zoom/focus motor (for focus control)	-	-	-	-		
			with transmission transmitter	-	-	-	-		
			with transmission transmitter and zoom/focus motor (for focus control)	-	-	-	-		
ZCAM	E2	LUMIX G X Vario 12-35mm f/2.8 II ASPH POWER OIS	Camera and lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	
			with zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	
			with transmission transmitter and zoom/focus motor (for zoom control)	√	-	√	-	Zoom/focus motor installed on right side	
SIGMA	fp	45mm F2.8	Camera and Lens	√	√	√	√		
			with zoom/focus motor (for focus control)	√	√	√	√	Zoom/focus motor installed on right side	
			with transmission transmitter	√	-	√	-		
			with transmission transmitter and zoom/focus motor (for focus control)	√	-	√	-	Zoom/focus motor installed on right side	